

## Technical Specifications

### Mechanical

<b>Dimensions</b>	141.8 x 127.6 x 30 mm (5.6 x 5 x 1.2")
<b>Weight</b>	520 g (1.1 lb)
<b>Enclosure material</b>	Polycarbonate

### Hardware

<b>Processor</b>	Quad-core ARM® Cortex®-A53 at 1.5 GHz
<b>System memory</b>	3 GB DDR4
<b>On-board storage</b>	16 GB eMMC
<b>Management interface</b>	Ethernet Bluetooth
<b>Networking interface</b>	LAN: (4) GbE RJ45 ports  WAN: (1) 1/2.5 GbE RJ45 port
<b>IDS/IPS throughput</b>	1 Gbps
<b>Power method</b>	USB type C (5V DC/3A)
<b>Supported voltage range</b>	100–240V AC
<b>Max. power consumption</b>	6.2W
<b>LCM display</b>	0.96" status display
<b>Button</b>	Factory reset
<b>Operating temperature</b>	-10 to 40° C (14 to 104° F)
<b>Operating humidity</b>	5 to 95% noncondensing
<b>Certifications</b>	CE, FCC, IC

### Gateway Features

<b>Performance</b>	Redundant WAN with failover and load balancing WiFi QoS with UniFi APs Application, domain, and country-based QoS Application and device type identification Additional internet failover with LTE Backup Internet quality and outage reporting
<b>Next-generation security</b>	Application-aware firewall rules Signature-based IPS/IDS threat detection Content, country, domain, and ad filtering VLAN/subnet-based traffic segmentation Full stateful firewall
<b>Advanced networking</b>	License-free SD-WAN WireGuard, L2TP and OpenVPN server OpenVPN client OpenVPN and IPsec site-to-site VPN One-click Teleport and Identity VPN Policy-based WAN and VPN routing DHCP relay Customizable DHCP server

IGMP proxy  
IPv6 ISP support

## **LEDs**

### **Ethernet**

Green: link/activity

## **Application Requirements**

### **Mobile app**

UniFi iOS™: Version 10.12.0 and later  
UniFi Android™: Version 10.11.2 and later