

Omada Unmanaged Switch | Datasheet

DS116GE


Omada 16-Port Gigabit Easy Smart Switch



Highlights

- 16× 10/100/1000Mbps RJ45 ports
- Plug and play, no configuration required
- Durable metal casing of superior quality and professional appearance
- Intelligent management via a web user interface and downloadable utility
- Green technology reduces power consumption

Product Pictures



Specifications

Hardware Features & Performance

Model		DS116GE
General	Standards	IEEE 802.3, IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x, IEEE 802.1q, IEEE 802.1p
	Interfaces	<ul style="list-style-type: none"> • 16 10/100/1000Mbps RJ45 Ports • AUTO Negotiation/AUTO MDI/MDIX
Performance	Forwarding Method	Store-and-Forward
	Switching Capacity	32 Gbps
	Forwarding Rate	23.8 Mpps
	MAC Address Table	8K
	Packet Buffer Memory	4.1 Mbit
Physical & Environment	Jumbo Frame	10 KB
	Power Supply	External Power Adapter (12V/1A)
	Network Media	<ul style="list-style-type: none"> • 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) • 100BASE-TX: UTP category 5 or above cable (maximum 100m) • 1000BASE-T: UTP category 5e or above cable (maximum 100m)
	Maximum Power Consumption	9.78 W
	Maximum Heat Dissipation	33.25 BTU/h

Hardware Features & Performance

Physical & Environment	Dimensions (W×D×H)	11.3*4.4*1.0 in. (286*111.7*25.4 mm)
	Fan Quantity	Fanless
	Installation	Desktop/Wall Mounting
	Operating Temperature	0°C~40°C (32°F~104°F)
	Storage Temperature	-40 °C~70 °C (-40 °F~158 °F)
	Operating Humidity	10%~90%RH, non-condensing
	Storage Humidity	5%~90%RH, non-condensing
	Certification	CE, FCC, RoHS

Software Features

Model	DS116GE
L2 Features	• IGMP Snooping
	• Static Link Aggregation
	• Port Mirroring
	• Cable Diagnostics
	• Loop Prevention
VLAN	• 32 VLANs (out of 4K VLAN IDs)
	• MTU/Port-Based/802.1Q VLAN
QoS	• 4 Priority Queues
	• Port-Based/802.1p/DSCP QoS
	• Bandwidth Control
	• Storm Control
Management	• Web-Based Graphic User Interface (GUI)
	• Easy Smart Configuration Utility

Disclaimer:

This Omada Easy Smart switch does not support Omada SDN central management.

Specifications are subject to change without notice. TP-Link is a registered trademark of TP-Link Technologies Co., Ltd. Other brands and product names are trademarks or registered trademarks of their respective holders. Copyright © 2024 TP-Link Technologies Co., Ltd. All rights reserved.