


1-Port XGS-PON Terminal

MODEL: XGZ032



Overview

TP-Link's XGZ032 XGS-PON Terminal provides up to 10 Gbps of uplink and downlink bandwidth simultaneously. It meets the higher bandwidth demand of various high-bandwidth services. It also reduces both capital and operating expenditure, protecting ISPs' existing infrastructure investments.



2.5G Wired Performance

Supports XGS-PON + 2.5 Gbps LAN port to enable fast 2.5G network connections



Bridge Mode

High-speed transparent transmission for the best signal



Remote Management

Supports OMCI, enables an operator to remotely configure and manage end-user devices



BOSA on Board Design

Support SC/APC port

Features



High Speed

Downstream and upstream rates up to 2.5Gbps



Easy Management


Supports OMCI (ONT Management Control Interface) remote management





Ease of Use

Quick and hassle-free installation
Intelligent power-saving method

Network Topology



Hardware Description



Specifications

Hardware

- Interface
1× 2.5GE LAN Port, 1× XGS-PON Port
- Button
Power On/Off Button, Reset Button
- External Power Supply
12V/1A
- Dimensions (W * D * H)
6.19 × 4.42 × 1.46 in (157.2 × 112.4 × 37.0 mm)
- Optical Module
Class E1
- GPON Standards
ITU-T G.9807.1, ITU-T G.988
- Transmitter
DFB Laser
- Receiver
PIN-TIA
- Data Rate
Upstream: 10 Gbps, Downstream: 10 Gbps
- Wavelength
Upstream: 1270nm, Downstream: 1577nm
- Distance
0 ~ 20Km Max
- Flash
128M NAND Flash
- RAM
128M DDR3

Software

- VLAN
802.1Q tag VLAN, Q in Q VLAN
VLAN transparent mode/VLAN translation mode/VLAN trunk mode
Authentication based on SN and Password
- IGMP
IGMP v1/v2/v3
- Security
AES Encryption, Packet Filter based on VLAN
- Management
Managed by Web, OMCI and Telnet,
Specified the management IP,
Reset to Factory default by Reset button or Web UI, Real-time statistics,
Optical Diagnostic, Dual Image,
Schedule Reboot, LED Schedule
- Advanced Functions
Upstream and Downstream FEC,
Dynamic Bandwidth Allocation(DBA) support NSR/SR,
Up to 32 T-CONTs and 256 GEM Ports,
Optical power detection, Dying Gasp,
Terminal Silent mechanism,
802.3az EEE Energy Conservation

Others

- Certification
CE, FCC, RoHS
- Environment
Operating Temperature: 0°C~40°C (32°F~104°F),
Storage Temperature: -40°C~60°C (-40°F ~140°F)
- Package Contents
1-Port XGS-PON Terminal XGZ032
Power Adapter
Quick Installation Guide